

PARFIX CARE REPAIR

TRETMAN ZAŠTITNIM SJAJEM / PROTECTIVE GLOSSY TREATMENT



Product benefits



RS
OSOBINE I NAMENA:

PARFIX care repair je zaštitni premaz na bazi poliuretanskih smola, namenjen vanrednom održavanju podnih obloga od drveta, smola i elastičnih materijala kao što su LVT, PVC i linoleum, naročito onih koje su jako oštećene i izložene intenzivnom hodaću. Za primenu na UV-lakovanim drvenim podovima preporučuje se prethodno testiranje radi provere prijanjanja na podlogu. PARFIX care repair daje tretiranoj površini novi izgled, koji karakterišu sledeća svojstva: površinska tvrdoća, žilavost i transparentnost.

- Izvanredno održavanje
- Površinska tvrdoća, žilavost i transparentnost

INFORMACIJE O PROIZVODU:

Temperatura primene: +10°C do +25°C

Način nanošenja: krpa od mikrovlakana

Razređivanje: ne razređuje se

Potrošnja: 60–70 m²/L

Sjaj / Mat:

MATT: 15 gloss

LACK: 60 gloss (1)

Stabilnost u skladištenju: 1 godina (2)

Čišćenje alata: vodom

(1) Mereno na vlažnom filmu debljine 90 mikrona, očvršćenom 7 dana na 20°C i 65% relativne vlažnosti

(2) U originalno zatvorenoj ambalaži, na temperaturi između +10°C i +25°C

Način upotrebe

Dobro promućkati pre upotrebe.

Površina koja se tretira mora biti savršeno čista, suva i bez voska i prašine. Krpu od mikrovlakana blago navlažiti vodom, naneti manju količinu proizvoda direktno na pod i ravnomerno rasporediti, vodeći računa da ne ostanu naslage ili višak materijala.

Napomene

Pod je prohodan nakon 2–3 sata.

Ne vraćati nameštaj i tepihe pre isteka 12–24 sata.

Sledeće pranje poda može se obaviti nakon 3 dana, koristeći odgovarajuća sredstva za čišćenje.

Preporučuje se probna primena radi provere prijanjanja na podlogu.

Pakovanje: 1 L

Transportno pakovanje: 12/480

ENG

PROPERTIES AND PURPOSE:

PARFIX Care Repair is a protective coating based on polyurethane resins, designed for emergency and intensive maintenance of wooden, resin-based, and elastic floor coverings such as LVT, PVC, and linoleum, especially those that are heavily worn and exposed to high foot traffic. For application on UV-lacquered wooden floors, preliminary testing is recommended to verify adhesion to the substrate. PARFIX Care Repair restores the treated surface, providing the following characteristics: surface hardness, toughness, and transparency.

- Extraordinary maintenance
- Surface hardness, toughness and transparency



PARFIX CARE REPAIR

TRETMAN ZAŠTITNIM SJAJEM / PROTECTIVE GLOSSY TREATMENT

www.tritonex.rs

office@tritonex.rs / Srete Mladenovića 2,
Kragujevac Serbia
@tritonexkg



PRODUCT INFORMATION:

Application temperature: +10°C to +25°C

Application method: microfiber cloth

Dilution: ready to use, do not dilute

Coverage: 60–70 m²/L

Gloss / Matte:

MATT: 15 gloss

LACK: 60 gloss (1)

Shelf life: 1 year (2)

Tool cleaning: with water

(1) Measured on a 90-micron wet film, cured for 7 days at 20°C and 65% relative humidity

(2) In original, unopened packaging, stored at temperatures between +10°C and +25°C

APPLICATION INSTRUCTIONS:

Shake well before use.

The surface to be treated must be perfectly clean, dry, and free of wax and dust.

Lightly moisten a microfiber cloth with water, apply a small amount of the product directly onto the floor, and spread evenly, ensuring no build-up or excess material remains.

NOTES:

The floor is walkable after 2–3 hours.

Do not replace furniture or carpets before 12–24 hours.

Floor cleaning may be carried out after 3 days, using suitable cleaning agents.

A test application is recommended to check adhesion to the substrate.

Packaging: 1 L

Transport packaging: 12 / 480