

PARFIX K22 PRIMER


JEDNOKOMPONENTNI PRAJMER NA BAZI VODE / SINGLE-COMPONENT WATER-BASED PRIMER

www.tritonex.rs

 office@tritonex.rs / Srete Mladenovića 2,
 Kragujevac Serbia
 @tritonexkg


TriTonex

Product benefits



RS

OSOBI NE I NAMENA:

PARFIX K22 PRIMER je jednokomponentni osnovni premaz na vodenano bazi i sastoji se od nano-dispergovanih čestica smola, koji garantuju visoku penetraciju premaza čak i u slučaju nisko upojnih podloga. Preporučuje se kao predpremaz, koji uklanja zaostalu prašinu i za površinsku konsolidaciju upojnih podloga, cementnih i anhidridnih /gipsanih/ samoizravnavajućih masa.

- VEZUJE ZAOSTALU PRAŠINU
- POVRŠINSKI KONSOLIDUJE PODLOGU
- UNUTRAŠNJA UPOTREBA

INFORMACIJE O PROIZVODU:

Način rada: pre upotrebe dobro promućkati. Nanosi se na čvrste podloge bez konstruktivnih nedostataka, trajno suve i očišćene od finih čestica prašine i drugih supstanci. Pre nanošenje podloga mora biti adekvatno suva. Predpremaz ne prolivati na podlogu, već ga nanositi pomoću valjka/četke ravnomerno po celoj površini. Po nanošenju ostaviti da se predpremaz potpuno osuši, pa tek onda nastaviti sa daljim radom. Nakon završenog rada alat se pere vodom. Koristi se u sistemu sa PARFIX CLASSIC i PARFIX SMP HYBRID lepkom.

Potrošnja: 100g/m²

Temperatura primene: +10°C do +25°C

Način primene: valjak od mikrofibera 8mm/četka

Razređivanje (ako je neophodno): vodom

Vreme sušenja: 3 - 4 sata (u zavisnosti od količine koja je naneta i upojnosti podloge)

Pogodno za: vezivanje zaostale prašine, površinsku konsolidaciju, površine podloge, na koju se nakon sušenja vrši lepljenje prekrivki od drveta lepkovima na bazi, akrilnih i reaktivnih smola

Skladištenje: skladištiti u originalnoj i dobro zatvorenoj ambalaži pri temperaturi od +10°C do +25°C, zaštićeno od direktne sunčeve svetlosti.

Napomena: Prilikom transporta i skladištenja zaštititi od mraza. Izbegavati duže izlaganje na temperature ispod 0°C. Proizvod je namenjen za profesionalnu upotrebu.

Pakovanje: 5kg

Transportno pakovanje: 1 / 70 pallet

ENG

PROPERTIES AND PURPOSE: PARFIX K22 PRIMER is a one-component water-based primer that consists of nano-dispersed resin particles, ensuring high penetration even into low-absorbent substrates. It is recommended as a primer, which removes residual dust and for the surface consolidation of absorbent substrates, cement and anhydride /gypsum/ self-leveling masses.

- BINDS REMAINING DUST • PROVIDES SURFACE CONSOLIDATION OF THE SUBSTRATE • INTERIOR USE

INFORMATION ABOUT THE PRODUCT:

Method of use: shake well before use. It is applied to solid surfaces without structural defects, permanently dry and cleaned of fine particles of grass and other substances. Before applying, the substrate must be adequately dry. Do not spill the primer on the substrate, but apply it using a roller/brush evenly over the entire surface. After application, leave the primer to fully dry, and only then continue with further work. After finishing the work, wash the tools with water. It is used in the system with PARFIX CLASSIC and SMP HYBRID adhesives.

Consumption: 100g/m²

Application temperature: +10°C to +25°C

Method of application: 8mm microfiber roller/brush

Dilution (if necessary): with water

Drying time: 3-4 hours (depending on the amount applied and the absorbency of the substrate)

Suitable for: binding of residual dust, surface consolidation, substrate surface, on which wooden coverings are glued after drying, with acrylic-based and reactive resins adhesives

Storage: store in the original and well-closed package at a temperature of +10°C to +25°C degrees, protected from direct sunlight.

Note: Protect from frost during transport and storage. Avoid prolonged exposure to temperatures below 0°C. The product is intended for professional use.

Package: 5kg



Tehnički podaci dati su u cilju postizanja optimalnih rezultata primenom proizvoda proizvođača Tritonex d.o.o. Kragujevac na osnovu dosadašnjih iskustva i ispitivanja u sertifikovanoj laboratoriji. Savetujemo kupcu da obavezno izvrši prethodno testiranje uzoraka za svoje potrebe. Proizvođač zadržava pravo na eventualne izmene. Za sve dodatne informacije obratite se našoj tehničkoj službi. / Технические данные предоставлены с целью достижения оптимальных результатов при использовании продукции, производимой компанией Tritonex d.o.o. Кragујевац на основании предыдущего опыта и испытаний в сертифицированной лаборатории. Мы рекомендуем покупателю провести предварительное тестирование образцов для своих нужд. Производитель оставляет за собой право вносить любые изменения. За дополнительной информацией обращайтесь в нашу техническую службу. / Technical data are provided in order to achieve optimal results using products manufactured by Tritonex d.o.o. Kragujevac based on previous experience and testing in a certified laboratory. We advise the customer to carry out preliminary testing of samples for his needs. The manufacturer reserves the right to make any changes. For any additional information, please contact our technical service.