

PARFIX RP 25

JEDNOKOMPONENTNI POLIURETANSKI LEPAK / ONE COMPONENT POLYURETHANE ADHESIVE

www.tritonex.rs

office@tritonex.rs / Srete Mladenovića 2,
Kragujevac Serbia
@tritonexkg



TriTonex

RS

OSOBI NE I NAMENA:

Jednokomponentni poliuretanski lepak, za popravku i fiksiranje starog drvenog parketa koji nije dobro pričvršćen i nestabilan ili se odvaja u delovima. Može da se koristi za lepljenje drveta za drvo, kao i drveta za beton ili malter. Koristi se za sve vrste podloga, parketa i lepkova za sanaciju šupljih mesta ispod parketa kao i za fiksiranje pojedinačnih letvica sa tačkastim povezivanjem plivajuće položenih podova. Takođe se koristi i za veće površine nanošenjem četkom ili valjkom.

- JEDNOKOMPONENTNI POLIURETANSKI LEPAK SPREMAN ZA UPOTREBU
- UČVRŠĆUJE ŠUPLJA MESTA ISPOD POLOŽENOG PARKETA
- ODLIČAN ZAPTIVAČ I VELIKA MOĆ LEPLJENJA STARIH DRVENIH PODOVA

INFORMACIJE O PROIZVODU:

Boja proizvoda: braon

Način rada: pre upotrebe lepak ostaviti da se prilagodi na sobnoj temperaturi. Lupkajući po površini, identifikovati i označiti područje koje je potrebno sanirati. U središte označenog područja odrediti mesto za bušenje i preko njega zalepiti lepljivu traku (krep traka) kako se ne bi osetila površina. Probušiti rupicu preko lepljive trake koristeći bušilicu promera 4mm. U izbušenu rupu injektirati lepak sa špricom. U slučaju sanacije većih površina potrebno je izbrusiti te površine kako bi se fuge što više proširile. Nakon toga špahtlom ili valjkom naneti lepak tako da što veća količina prodre u fuge. Nakon sušenja ponoviti postupak ako je potrebno. Nakon toga ishoblovati kompletno sanirane površine i nastaviti sa ostalim fazama obrade parketa.

Potrošnja: 200-300g/m² u zavisnosti od površine koja se tretira.

Nanošenje: injektiranjem, špahtlom ili valjkom

Temperatura primene: +10°C do +25°C

Hoblovanje: 1 do 3 dana

Prohodnost: posle 24h

Skladištenje i rok trajanja: u originalnom pakovanju na suvom prostoru na temperaturi od +15°C do +25°C

Pakovanje: 5L / **Transportno pakovanje:** 1/70

ENG

PROPERTIES AND PURPOSE:

One-component polyurethane adhesive, for repairing and fixing old wooden parquet that is not well attached and unstable or partially separated. It can be used for gluing wood to wood, as well as wood to concrete or mortar. It is used for all types of substrates, parquets and adhesives for the rehabilitation of hollows under the parquet as well as for fixing individual slats with point connection of floating floors. It is also used for larger areas by applying it with a brush or roller.

- ONE-COMPONENT POLYURETHANE ADHESIVE, READY FOR USE
- STRENGTHENS HOLLOWS UNDER THE LAYED PARQUET
- EXCELLENT SEALER AND GREAT ADHESIVE POWER FOR OLD WOODEN FLOORS

INFORMATION ABOUT THE PRODUCT:

Product color: brown

Method of use: before use, leave the adhesive to adjust at room temperature. Patting on the surface, identify and mark the area that needs to be repaired. Determine a place for drilling in the center of the marked area and stick adhesive tape (crepe tape) over it to protect the surface. Drill a hole through the adhesive tape using a 4mm diameter drill. Inject adhesive with a syringe into the drilled hole. For rehabilitating larger surfaces, it is necessary to sand those surfaces so that the joints expand as much as possible. Next, apply the adhesive with a spatula or a roller to ensure full penetration into the joints. After drying, repeat the procedure if necessary. In the end, completely repaired surfaces should be sanded and other stages of parquet processing should be continued.

Consumption: 150-200ml/m² depending on the surface being treated.

Application: injection, spatula or roller

Application temperature: +10°C to +25°C

Sanding: 1 to 3 days

Passability: after 24h

Storage and shelf life: originally closed and stored in dry area, at temperatures from +15°C to +25°C

Package: 5l



Product benefits



24h

SOLVENT free



1K
A

200-300g
m²



Tehnički podaci dati su u cilju postizanja optimalnih rezultata primenom proizvoda proizvođača Tritonex d.o.o. Kragujevac na osnovu dosadašnjih iskustva i ispitivanja u sertifikovanoj laboratoriji. Savetujemo kupcu da obavezno izvrši prethodno testiranje uzoraka za svoje potrebe. Proizvođač zadržava pravo na eventualne izmene. Za sve dodatne informacije obratite se našoj tehničkoj službi. / Технические данные предоставлены с целью достижения оптимальных результатов при использовании продукции, производимой компанией Tritonex d.o.o. Кragуевац на основании предыдущего опыта и испытаний в сертифицированной лаборатории. Мы рекомендуем покупателю провести предварительное тестирование образцов для своих нужд. Производитель оставляет за собой право вносить любые изменения. За дополнительной информацией обращайтесь в нашу техническую службу. / Technical data are provided in order to achieve optimal results using products manufactured by Tritonex d.o.o. Kragujevac based on previous experience and testing in a certified laboratory. We advise the customer to carry out preliminary testing of samples